



Product Datasheet

11103K/W/W



3W LED Dark Light Recessed adjustable spot, IP20.

Requires 350mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads




Dimensions



Must be ordered separately



89004



89004T

Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The 3W Mini Lighter
Order Code	11103K/W/W
Colour	White
Material	Aluminium
Shape	Circular



Height	52mm
Diameter	52mm
Cutout Hole Diameter	42mm
Recessed Ceiling	Yes
Depth Required	60mm
Indoor	Yes
Adjustable	1 Direction

Electrical Characteristics

Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	8,4V
Safety Class	
Power(Watts)	3W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	1
Cable Length	40cm
F Mark	

Illumination Data

Colour Temperature	3000K
Lumen Output	240lm
Light Efficiency	80lm/W
CRI	90
Beam Angle	30°

Illumination Diagram
Dark Light



Yes

Packing Info

Box Length
Box Width
Box Height
Pcs/Carton
Barcode
HS Code

5,5cm

5,5cm

5,6cm

100

5291889070047

9405409900

Certification & Warranty

Warranty
Weee Directive

5 Years

Yes

